

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
1 February 2001 (01.02.2001)

PCT


(10) International Publication Number
WO 01/07331 A1(51) International Patent Classification⁷: **B65D 25/40**(21) International Application Number: **PCT/US99/16641**(22) International Filing Date: **23 July 1999 (23.07.1999)**(25) Filing Language: **English**(26) Publication Language: **English**(71) Applicant (for all designated States except US):
SCHOLLE CORPORATION [US/US]; 19500 Jam-
boree Boulevard, Irvine, CA 92715 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **SAVAGE, Chester**
[US/US]; 6 Harvest, Irvine, CA 92604 (US); **ANDER-**
SON, Mark [AU/US]; 587 Cardiff, Irvine, CA 92606 (US).
SANDVOSS, Silvio [US/US]; 23481 Bending Oak Court,
Murieta, CA 92562 (US).(74) Agent: **MILLER, Terry, L.**; 24832 Via San Fernando,
Mission Viejo, CA 92692 (US).(81) Designated States (*national*): AE, AL, AM, AT, AU, AZ,
BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE,
ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP,
KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD,
MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD,
SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ,
VN, YU, ZA, ZW.(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM,
AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT,
BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,
NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— With international search report.

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.(54) Title: **FLUID COUPLING WITH ROTARY ACTUATION**

(57) Abstract: A two-part coupling structure (22, 32) includes a male coupling part (32) and a female coupling part (22) which are mutually engageable to open fluid communication between the coupling parts (22,32). For example, the coupling parts (22, 32) may be used to establish fluid communication between a container (12) and a conduit (14). The coupling parts (22, 32) are disengageable from one another to discontinue fluid communication between them, and also to close communication between ambient and each of the container (12) and the conduit (14). The male coupling part (32) includes a mounting structure (44a-44e) for supporting on the female coupling part (32), and also includes a guide structure (44) effective to guide a male probe portion (36) of the male coupling part (32) into engagement with the female coupling part (22). A rotary actuator member (34), preferably in the form of a handnut is included in the male coupling part (32), and is effective upon rotation of cause axial relative movement of the male probe portion (36) into or out of engagement with the female coupling part (22). A considerably lowered manual engagement and disengagement force is provided, along with increased convenience and ease of use for the coupling structure.

WO 01/07331 A1